

eSMART107 Tech-Note

HMI 7" TFT Resistive touch, 4 GB Flash, 2x Ethernet

- 7" TFT color display, resolution 800x480 pixel, 64K colors. Dimmable LED backlight
- Resistive touchscreen
- 2 Ethernet ports
- 2 CAN ports
- 4 Serial ports
- 2 USB ports



Highlights

eSMART107 combines top performance and plenty connectivity features in a compact design.

It is an ideal platform for integrated HMI and control applications. The product has been designed as IoT edge device with the combination of a powerful controller with networking capability and outstanding communication options including client/server OPC UA.



The eSMART HMI products have been designed to run the JMobile software.

- JMobile runtime included
- Requires JMobile V2.6 or higher
- Supports Corvina Cloud secure connectivity with full network separation
- OPC UA Server and Client
- Optional CODESYS V3 runtime with choice of EtherCAT, Profinet, Ethernet IP, Modbus TCP and CAN networks



eSMART107 - Technical Data



System Resources	
Display - Colors	7" TFT 16:9 - 64K
Resolution	800x480, WVGA
Brightness	200 Cd/m ² typ.
Dimming	to 0%
Touchscreen	Resistive
CPU	32-bit RISC dual core - 800 MHz
Operating System	Linux RT
Flash	4 GB
RAM	1 GB
Real Time Clock, RTC Back-up, Buzzer	Yes, Yes, No
Interface	
Ethernet port	2 (port 0 - 10/100, port 1 - 10/100)
USB port	2 (Host V2.0, max. 100 mA)
Serial port	2 (RS-232), 2 (RS-422/RS-485 isolated), 2 (CAN 2.0b isolated)
SD card	No
Expansion	No
Ratings	
Power supply	24 Vdc (10 to 32 Vdc)
Current Consumption	0.3 A at 24 Vdc (max.)
Input Protection	Electronic
Battery	Rechargeable battery, not user-replaceable
Environment Conditions	
Operating Temp	0 to +50°C (vertical installation)
Storage Temp	-20°C to +70°C
Operating / Storage Humidity	5-85% RH, non condensing
Protection Class	IP66 (front), IP20 (rear) - Type: 2, 4X
Dimensions and Weights	
Faceplate LxH	187x147 mm (7.36x5.79")
Cutout AxB	176x136 mm (6.93x5.35")
Depth D+T	29+5 mm (1.14+0.19")
Weight	0.875 Kg
Approvals	
CE	Electromagnetic Compatibility (EMC) - Directive 2014/30/EU
UL	cULus: UL508
DNV-GL	Yes
EU RO MR	Yes
RCM	Yes



- | | |
|----------------------------|----------------------------------|
| 1 Power Supply | 6 USB port |
| 2 Serial port RS-485 + CAN | 7 Ethernet port 0 (10/100 Mb) |
| 3 Serial port RS-485 + CAN | 8 Ethernet port 1 (10/100 Mb) |
| 4 Serial port 2x RS-232 | 9 DIP switch port configuration |
| 5 USB port | 10 DIP switch port configuration |



Ordering Information

Model	Part Number	Description
eSMART107	+ESMA107U301	HMI 7" TFT, 800x480, Resistive touch, 4 GB Flash, 2x Ethernet, JMobile runtime